

YJ47052

Multi-Conductor PROFIBUS CABLE



For more information please
call
1-800-Belden1

See Put-ups and Colors

Description:

22 AWG Solid Bare Copper Conductor, Foam polyethylene insulation, twisted pair, overall Beldfoil® plus a tinned copper Braid shield(65% coverage), PVC jacket

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	2
Conductor Stranding	1/0.66mm
Conductor Material	BC – Bare Copper

INSULATION:

Insulation Material	FPE-Foam polyethylene
Nom. Insulation Diameter of	2.50 mm

OVERALL CABLING:

Overall Cabling Lay Length	70 mm
Overall Cabling Color Code Chart:	Green*Red
Overall Shield Type	Tape
Overall Shield Material	AL-Aluminum Foil-Polyester Tape
Overall Shield Coverage (%)	100
Overall Shield Type	Braiding
Overall Shield Material	TC – Tinned Copper
Overall Shield Coverage (%)	65% Nom.

OUTER JACKET:

Outer Jacket Material	PVC –Polyvinyl Chloride
Nom. Outer Jacket Wall Thickness	1.00 mm

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	8.00 mm
--------------------------	---------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	- 20°C To + 75°C
Temperature Rating	+ 75°C @ maximum voltage

YJ47052 Multi-Conductor PROFIBUS CABLE

Voltage Rating	300V @ maximum temperature
Bulk Cable Weight	72 kg/km

APPLICABLE SPECIFICATION AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

EU RoHS Compliant (Y/N)	Y
EU RoHS Compliance Date	June 2007

FLAME TEST:

Flame Test	VW-1
------------	------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Conductor DC Resistance @ 20°C	16.0 Ω/1000FT
Max. continues current per conductor (25°C)	2.3 A
Nom. Mutual Capacitance @ 1KHz	19.5 pF/FT
Nom. Inductance	0.282 μ H/FT
Nom. Impedance @3~20MHz	150 Ω
Nom. Velocity of propagation	78 %
Attenuation	

Frequency	Attenuation (dB/100ft) Nom.	Attenuation (dB/100m) Max.
0.20	0.27	1.10
4.00	0.67	2.65
16.00	1.37	5.40

Test voltage cond.~cond.(DC)	2.5 kv/3s
Test voltage cond.~screen(DC)	1.5 kv/3s
Min. bengding radius	10xCable diameter

PUT-UPS AND COLORS:

Item	Description	Put-Up (metre)	Ship Weight (kg)	Jacket Color
YJ47052 0601000	1Pair 22AWG SHIELDED FPE/PVC	305	24.5	CHROME
YJ47052 0071640	1Pair 22AWG SHIELDED FPE/PVC	500	38.0	VIOLET
YJ47052 0073280	1Pair 22AWG SHIELDED FPE/PVC	1000	78.0	VIOLET

Revision Number: 0

Revision Date: 2009-11-10

YJ47052

Multi-Conductor PROFIBUS CABLE

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & amp; Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.