



PW ES-1573
Prestoflex Welding Cable
125°C EPDM

Features

Conductors available in tinned or copper
Insulation: 125°C EPDM
RoHS and REACH Compliant

Product Design Options

Custom strand constructions
Custom diameter to meet design criteria
Various colors
Packaging options: reels

Applications

Cables used for welding electrical

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (in)	Nom OD (in)	Nom. Wall (in)	Min. Wall (in)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
6	280	30	0.185	0.356	0.080	0.056	127	80
4	440	30	0.237	0.403	0.080	0.056	183	128
2	704	30	0.297	0.485	0.090	0.063	268	192
1	880	30	0.345	0.529	0.095	0.067	340	258
1/0	1112	30	0.380	0.591	0.105	0.074	432	324
2/0	1408	30	0.429	0.635	0.105	0.074	520	409
3/0	1760	30	0.465	0.685	0.105	0.074	646	518
4/0	2224	30	0.544	0.764	0.115	0.081	810	653
250MCM	2368	30	0.577	0.825	0.115	0.081	942	764

REV:-1- 3/30/2011

Customer Service Group

1 Prestolite Drive
Paragould, Arkansas 72450
Phone: 800-952-3842 870-236-8141
Fax: 870-239-6139
Web: www.prestolitewire.com