



Description: Five 18 AWG Conductors
 Overall PVC Jacket

Date: 6/29/2016

JM Part Number: TBD
Reference: TBD

Components Five 18 AWG Insulated Conductors

Conductor: 18 AWG, 16/30 bare copper

Insulation: .022" nominal wall of PVC (see color code) .089"

Overall Cable Construction

Cabling: Five conductors twisted together with FRPP Fillers

Binder: Fleece tape

Jacket: .035" nominal wall of pressure extruded Gray PVC .315"

Print (Black Inkjet)

WALDMANN www.waldmannlighting.com E66440 5/C 18 AWG 9\ AWM
 AWM 2587 90C 600V --- LL41103 CSA AWM I/II A/B 90C 600V
 FT1 --- CE ROHS

Color Code

- | | |
|----------|-----------|
| 1. Black | 4. Purple |
| 2. White | 5. Gray |
| 3. Green | |

Requirements

Temperature: 90C
 Voltage: 600V

Approvals: UL AWM Style 2587
 CSA AWM, FT1
 CE-LVD and RoHS Compliant
 (2011/65/EU)

| | | | | |
|-------------|--------|-----------|--------|---------------|
| Written By: | rac/ad | 6/29/2016 | Rev. 0 | Initial Issue |
| Revised By: | | | | |
| Revised By: | | | | |
| Revised By: | | | | |