



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 2/10/2016

Issue: 1

Construction

Description:	4/Pr 22 19/34 TC PVC/TPV OAFS + Drain	Diam. (In)
Component:	8 Conductors (4 pair)	
Conductor:	22 AWG 19/34 Tinned Copper to ASTM B-8	0.0297"
Insulation:	0.01" General Purpose PVC	0.0497"
Color Code:	Blk/Wht, Red/Blue, Grn/Yel and Gray/Violet	0.0497"
Cable Assembly:	Twist to 4 twisted Pairs	0.082"
Cable Assembly:	Bunch Cable the 4 Twisted Pairs	0.198"
Fillers	Fibrillated polypropylene or solid fillers for roundness (optional)	0.198"
Drain Wire:	24 7/32 TC	0.198"
Shield:	Aluminum Mylar Foil Shield	0.201"
Tape:	Non-Woven Separator Tape for Strip-Ability (optional)	0.201"
Jacket:	0.032" Santoprene TPV	0.265"
Jacket Color:	Black	0.265"

Print:

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>		
UL	AWM-20237	105°C	300	FT-2		
Canadian cRU	AWM	105°C	300	FT-2	I/II	A/B

Environmental Compliance

- EU Directive 2011/65/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65: