

**ALPHA WIRE**

Part Number: 16-2082

Issue:

B

Page 1 of 1 Pages

Issue Date:

7/18/2016

**Cable Specification**

**Component 1**                    3 COND  
Conductor:    18 (16/30) AWG TC  
Insulation:    0.016" Wall, Nom. TPE  
Color Code:    3 SOLID COLORS/ 0 STRIPED/ 0 NUMBER CODED

**Final Assembly**                3 Components  
Core Wrap:    NWP Tape, 25% Overlap, Min.  
Shield:        AM Foil Tape, 25% Overlap, Min.  
Drain Wire:    24 (7/32) AWG TC  
Jacket:        0.045" Wall, Nom., TPE  
Jacket OD:     0.269"  
Jacket Color:   SLATE

**Approvals**

UL:    AWM/STYLE 21918  
       PLTC  
       AWM/STYLE 20237  
CSA:   c(RU) AWM I/II A/B  
       FT1  
MIL:   NONE  
CE Compliant: YES  
ROHS Compliant: YES  
REACH Compliant: NO

**Miscellaneous**

Temperature:    125 C  
Voltage:        300 V<sub>RMS</sub>  
Put Ups:        1000 FT PUTUP  
Requested Quantity: 10000Ft.

**Application Notes**

CUSTOM PRODUCTS ARE NON-CANCELLABLE &amp; NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

**PROPRIETARY NOTICE**

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.