



# PRODUCT DATA SHEET

Controlled Document - Engineering Drive


1530 Shields Drive  
Waukegan, IL 60085  
Toll-Free (800) 323-9355  
Fax: (847) 689-1192

**PART NUMBER:** 96238  
**DESCRIPTION:** 22/4 SOLID CM/CL2 CMH FT1 CABLE  
**CONSTRUCTION:** This cable consists of four bare copper insulated conductors cabled with an overall jacket.  
**APPROVALS:** UL Standard 13 and 444, NEC Articles 725 and 800.  
**APPLICATION:** Class 2 Power Limited Circuit Cable and Communications Cable for General Purpose Applications

## Construction Parameters:

Conductor 22 AWG Bare Copper  
Stranding Solid  
Insulation Material Foam Polypropylene  
Insulation Thickness 0.006" Nom.  
Insulated Conductor Diameter 0.037" Nom.  
Number of Conductors 4  
Lay Length Parallel  
Jacket Material PVC  
Jacket Thickness 0.014" Nom.  
Overall Cable Diameter 0.117" Nom.  
Approximate Cable Weight 14.4 Lbs/1M' Nom.  
Flame Rating UL 1581 Vertical Tray Flame Test

## Cable Cross-Section



## Electrical Properties:

Temperature Rating -20°C to 75°C  
Operating Voltage 300 V RMS Max.  
Capacitance Between Conductors @ 1 KHz 20 pF/ft Nom.  
Capacitance Between Conductors to Shield @ 1 KHz -----  
DC Resistance per Conductor @ 20°C 16.90 Ohms/1M' Nom.

Insulation Colors Black Yellow Red Green  
Jacket Color Gray, White, Black (Other colors available for minimum order)

Legend (Surface Ink Print) COLEMAN CABLE 96238 22 AWG C(ETL)US (ETL CODE) CM/CL2 75C SUN RES - CMX  
OUTDOOR - CMH FT1 -- XX/XX/XX (MONTH/DAY/YEAR) HH:MM (HOUR/MINUTE)

This product complies with European Directive 2011/65/EU (RoHS-2)  
On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.  
The jacket is sequentially footmarked.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: February 19, 2013