



Marking

E148000 AWM STYLE 2464 20AWG 80°C 300V VW-1 - - -
 AWM I/II A/B 80°C 300V FT1 -LF- PCXX

Color

Cores Insulation :
 1.Black-Brown 2.Red-Orange 3.Yellow-Green 4.Blue -Purple
 5.Gray-White 6.Pink-Light Green 7.Light Blue-Light Gray
 8.White/Black-White/Brown 9.White/Red-White/Orange
 10.White/Yellow-White/Green

Jacket:
 According to the customer's requirements.

Description

Rated Voltage (V)	300
Rated Temperature (°C)	80
Product Standard Certification	UL
Flammability Test	VW-1

Application
 For internal wiring or external wiring of Class 2 systems equipment and electronic equipment.

Reference Standard
 UL758, UL1581, CSA C22.2 No210

Performance

Electrical Characteristics:

Dielectric Strength (kV/min)	2.0
Max. DC Resistance at 20°C (Ω/km)	36.7

Construction

10 Pair	Stranded Tinned Copper
AWG	20
Construction	26/0.16
Stranded Dia. (mm)	0.94
Insulation	SR-PVC
Nom. Thickness (mm)	0.23
Insulation Dia. (±0.10mm)	1.45
Twisted	2C
Filler	Yes
Cabling	10P+Filler
Al-mylar (Coverage, %)	100
Jacket	PVC
Nom. Thickness (mm)	0.76
Min. Thickness (mm)	0.61
Outer Dia. (±0.30mm)	10.60

Mechanical Characteristics:

Test Object	Jacket
Test Material	PVC
Before Aging Tensile Strength (Mpa)	≥ 10.30
Elongation (%)	≥ 100
Aging Condition (°C)	113±2°Cx168hr
After Aging Tensile Strength (Mpa)	≥ 70% of original
Elongation (%)	≥ 65% of original

LQL-16105

Par No. :

Packing: 500M/R Customer Name:

Ref. spec No. : Rev.: 0

Revision History



LTK INTERNATIONAL LIMITED
 Suite 502, Concordia Plaza, 1 Science Museum Road
 Tsimshatsui East, Kowloon, Hong Kong
 Tel : (852) 2382 1133 Fax : (852) 2480 6327
 Email : sales@ltkable.com URL : www.ltkable.com

- LTK Electric Wire (Huizhou) Ltd
- Huizhou LTK Electronic Cable Ltd
- LTK Electric Wire (Jintan) Ltd
- LTK Cable (Chongqing) Ltd
- Dalian LTK Electric Wire Ltd

Prepared by: LQL 2016.08.24 Table No.:TFA04 Rev.: 6
 Approved by: KAKA 2016.08.24 Page 1 of 1

* Usage instruction:
 Not to be used directly in corrosive environments such as strong acids and strong alkaline. not be immersed in water or in a high humidity environment.
 not be exposed in the sunlight outdoor. It is suggested the wiring minimum bending radius shall be 5 times OD and more, and can not be used in strong stress conditions. The wire needs to be stored indoors, in a dry and ventilated environment. If there's some special requirements for wire , please contact with our sales .
 When customers purchase our products,they should test to verify whether the products is applicable to the usage.