


26 AWG (7X34) STRANDED TELEPHONE CORDAGE (FLAT), PVC JACKET  
 UL20251 FILE No UL E134689, CUL

PART NUMBER	No. OF CONDUCTORS	OUTSIDE DIAMETER IN INCHES (± 0.05)	JACKET THICKNESS IN INCHES	
			INCHES	MM
UL300-4	4	.090 X .185	.022	.55

CONSTRUCTION			ELECTRICAL CHARACTERISTIC	
CONDUCTOR	26 AWG STRANDED BARE COPPER		DC RESISTANCE ( OHM/1M AT 20°C )	.1367 MAX.
INSULATION CONSTRUCTION	COLOR-CODED POLYPROPYLENE		RESISTANCE OF INSULATION	1000M OHM/KM AT 20°C
	DIAMETER	.040±.002	DIELECTRIC TEST	500 V/1 MIN. AC
	AVG. THICKNESS	.009±.002	SPARK TEST	2KV
CONDUCTOR CONSTRUCTION	DIAMETER OF WIRE	.006	RATING	60° 150V
	NUMBER OF STRANDS	7	TEMPERATURE RATING	
	LAY LENGTH OF STRAND	20		
JACKET	PVC, SILVER SATIN		COLD BEND TEST	NO CRACK AT -10° c/H
			FLAME TEST	SELF EXTINGUISH 60°C / 150V PASSES VW-1 VERTICAL FLAME TEST
			FLEXIBLE BEND TEST	NO FRACTURE 100°C 168H

NOTE:

1. PACKING: 1000FT ON PAPER SPOOL
2. UL LABELS ON SPOOL



DESCRIPTION: 26 AWG FLAT TELEPHONE CORDAGE, 4 COND.			CHK:	APRVD:	REV.: E	DWG BY: A. MEDINA	
COLOR: SILVER	THIS DRAWING IS THE EXCLUSIVE PROPERTY OF SHAXON INDUSTRIES, INC. ITS ACCEPTANCE CONSTITUTES AN AGREEMENT THAT SHOULD BE TREATED AS A STRICTLY CONFIDENTIAL DOCUMENT TO BE USED FOR NO OTHER PURPOSE THAN TO AID IN THE ASSEMBLY OR OPERATION OF UNITS FURNISHED BY OR FOR SHAXON IND. INC. OR OTHERWISE AS EXPRESSLY AUTHORIZED IN WRITING BY SHAXON IND. INC. THAT IT IS RETURNED UPON REQUEST AND IS NOT TO BE COMMUNICATED, DISCLOSED OR COPIED EXCEPT AS EXPRESSLY AUTHORIZED IN WRITING BY SHAXON INDUSTRIES INC. AutoCAD Release 12 c1a, Serial #: 110-10626948			DATE: 01/24/2017		DO NOT SCALE	
MATERIAL: PVC				PART NO.:		UL300-4	
DWG NO. D.S. 1297							