


CONTINUOUS FLEX CABLES

also available with green-yellow insulation and gray jacket



S 900 Continuous flex oil resistant power supply cable for small bend radius applications



Marking for S 900 07671362:

SAB BRÖCKSKES · D-VIERSEN · 07671362 16.0 mm² S 900 6 AWG AWM Style 10455 90°C 600V CSA AWM I/II A/B 90°C 600V FT1 FT2

S 900 is an ultra flexible 600 V, UL recognized, CSA approved cable designed for power applications. The design incorporates the IEC 60228 class 6 super fine wire stranding which provides excellent flexibility. The specially blended PVC jacket passes the stringent VDE test 0281 part 1 and HD 21.1 oil test providing the best oil resistance available for a PVC jacket. Recommended applications are power supply cables for spindle motor, cable handling systems requiring power cable, and interconnect wire from power supply to the machine.

B
7

Construction:

Conductor:	bare copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 6
Insulation:	PVC, TI2 acc. to DIN VDE 0281 part 1 + HD 21.1
Wrapping:	non-woven tape
Jacket material:	PVC, TM5 acc. to DIN VDE 0281 part 1 + HD 21.1
Jacket color:	black

Outstanding features:

- highly flexible single conductor for use in cable tracks
- UV resistant jacket

Technical data:

Nominal voltage:	DIN VDE: Uo/U 0.6/1 kV	
Voltage:	UL/CSA: 600 V	
Min. bending radius continuous flexing:	7.5 x O.D.	
Radiation resistance:	8 x 10 ⁷ cJ/kg	
Temperature range static:	DIN VDE: -40/+70°C	UL/CSA: up to +90°C
flexing:	+5/+70°C	
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2, UL VW-1, CSA FT1 and FT2	
Oil resistance:	very good - PVC TM5 acc. to DIN VDE 0281 part 1 + HD 21.1	
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/29	

Color of insulation: ➤ black

item no.	no. of conductors x cross section n x mm ²	AWG/MCM	outer-ø ± 5% inch	outer-ø ± 5% mm	cable weight ≈ lbs/mt	ampere at 30°C
07671315	1 x 1.50	16 (≈ 84/34)	0.193	4.9	26	24
07671325	1 x 2.50	14 (≈ 140/34)	0.228	5.8	37	32
07671340	1 x 4.00	12 (≈ 224/34)	0.260	6.6	52	42
07671360	1 x 6.00	10 (≈ 186/32)	0.287	7.3	70	54
07671361	1 x 10.00	8 (≈ 320/32)	0.358	9.1	108	73
07671362	1 x 16.00	6 (≈ 504/32)	0.398	10.1	155	98
07671363	1 x 25.00	4 (≈ 760/32)	0.472	12.0	226	129
07671364	1 x 35.00	2 (≈ 1083/32)	0.539	13.7	305	158
07671365	1 x 50.00	1 (≈ 703/28)	0.622	15.8	425	198
07671385	1 x 54.00	1/0 (≈ 779/28)	0.642	16.3	455	213
07671386	1 x 68.00	2/0 (≈ 969/28)	0.673	17.1	530	226
07671366	1 x 70.00	2/0 (≈ 988/28)	0.681	17.3	540	245
07671387	1 x 86.00	3/0 (≈ 1218/28)	0.776	19.7	696	263
07671367	1 x 95.00	3/0 (≈ 1340/28)	0.827	21.0	770	292
07671388	1 x 108.00	4/0 (≈ 1528/28)	0.886	22.5	864	313
07671368	1 x 120.00	4/0 (≈ 1680/28)	0.898	22.8	942	344
07671389	1 x 127.00	250 MCM (≈ 1799/28)	0.917	23.3	1001	370
07671369	1 x 150.00	250 MCM (≈ 2122/28)	0.969	24.6	1158	391
07671390	1 x 152.00	300 MCM (≈ 2154/28)	0.969	24.6	1158	396
07671391	1 x 177.00	350 MCM (≈ 1443/26)	1.051	26.7	1378	430
07671370	1 x 185.00	350 MCM (≈ 1472/26)	1.051	26.7	1401	448
07671392	1 x 204.00	400 MCM (≈ 1628/26)	1.197	30.4	1620	470
07671393	1 x 232.00	450 MCM (≈ 1850/26)	1.240	31.5	1809	490
07671371	1 x 240.00	450 MCM (≈ 1910/26)	1.240	31.5	1856	528
07671394	1 x 255.00	500 MCM (≈ 2035/26)	1.252	31.8	1962	535
07671395	1 x 283.00	550 MCM (≈ 2257/26)	1.323	33.6	2284	560
07671372*	1 x 300.00	550 MCM (≈ 2388/26)	1.350	34.3	2286	608
07671396*	1 x 306.00	600 MCM (≈ 2442/26)	1.350	34.3	2329	613

*from 283 mm² only UL recognition.

Other dimensions and colors are possible on request.

E-mail: info@sabcable.com



Web site: www.sabcable.com