

156-00455

HellermannTyton



Article Number: 156-00455

Description: Arrowhead Push-Mount Cable Tie, 7.9" Long, 50lb Tensile, .25"-.26" Hole, .03"-.05" Pnl, PA46/PEEK, Gray/Bge, 100/pkg

Base Data	
Local Order Number	156-00455
Type	T50ROSP1SFT6.5
Color	Gray (GY)
Features and benefits	<ul style="list-style-type: none"> • PEEK material provides excellent resistance to extreme temperature environments. • Two piece assembly allows the mount to slide along the strap ensuring proper orientation. • Arrowhead style mount provides low insertion and high extraction force. • Arrowhead disc protects against dirt and other impurities.
Quantity Per	bag
Product Description	HellermannTyton's arrowhead push mount tie assembly is a two piece design allowing the mount to slide along the strap of the tie to ensure proper orientation. The arrowhead mount is designed for low insertion into a pre-drilled hole, while providing a high extraction force. The disc also protects against dirt and other impurities.
Short Description	Arrowhead Push-Mount Cable Tie, 7.9" Long, 50lb Tensile, .25"-.26" Hole, .03"-.05" Pnl, PA46/PEEK, Gray/Bge, 100/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	225.0N
Length L (Imperial)	7.9"
Length L (Metric)	200.0mm
Length L2 (Imperial)	0.34"
Length L3 (imperial)	0.63"
Length L3 (metric)	16mm
Fixation Method	Arrowhead
Identification Plate Position	none
Length L2 (Metric)	8.6mm
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.18"

156-00455



Product Dimensions	Width W (Metric)	4.6mm
	Width W3 (Imperial)	0.33"
	Width W3 (Metric)	8.4mm
	Height H (Imperial)	0.59"
	Height H (Metric)	15.0mm
	Height H2 (Imperial)	0.6"
	Bundle Diameter Min. (Imperial)	0.04"
	Bundle Diameter Min. (Metric)	1.0mm
	Bundle Diameter Max. (Imperial)	1.8"
	Bundle Diameter Max. (Metric)	45.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.05"
	Panel Thickness Max. (Metric)	1.3mm
	Panel Thickness Min. (Imperial)	0.03"
	Panel Thickness Min. (Metric)	0.7mm
	Mounting Hole Diameter D (Metric)	6.3 - 6.7 mm
	Mounting Hole Diameter D Min. (Imperial)	0.25"
	Mounting Hole Diameter D Max. (Imperial)	0.26"
	Thickness T (Imperial)	0.05"
Thickness T (Metric)	1.3mm	
Material and Specifications		
	Material	Polyetheretherketone (PEEK)
	Material Shortcut	PA46
	Material Cable Tie	Polyamide 4.6 (PA46)
	Flammability	UL 94 V2
	Operating Temperature	-67°F to +464°F (-55°C to +240°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987

156-00455

HellermannTyton

Logistic and Packaging	Content Unit (BMEcat)	pieces
	Weight (Metric)	1.4kg