

**1. CONDUCTOR:**

- 1.1 Size and Material: 6 133/27 AWG (19 x 7) silver-plated copper wire.
- 1.2 O.D.: .202" nom.

**2. INSULATION:**

- 2.1 Extruded FEP.
- 2.2 Wall thickness: .030" nom.
- 2.3 Marking on insulation: as per UL & CSA Standards.
- 2.4 O.D.: .262" nom.
- 2.5 Color: as per order (replace X in the part number and the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 200°C (UL)/180°C (CSA)




**4. REFERENCES:**

- 4.1 UL Subject 758 (AWM), Style 1330.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.								This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: 		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com		
									Date: July 26, 2016				
									Verified: 		Description: <b>XK30S6133/27-X</b>		
									Date: July 26, 2016				
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.									Size: <b>A</b>	Scale: ---	Page: 1 of 1	Code Ident. No: <b>57104</b>	Specification No.: <b>Q00652-X</b>