



# Specification Sheet

## Lake Cable Part #: C262T-2464

**Description:** 26 AWG 2 conductors 7 strands tinned copper wire, SRPVC insulation, unshielded, with an overall PVC jacket.

### 1. Conductor

- 1.1. AWG Size & Stranding: 26 AWG 7 Strands Class B
- 1.2. Material: Annealed Tinned Copper
- 1.3. Conductor Count: 2 Conductors

### 2. Insulation

- 2.1. Material: Semi-Rigid Polyvinylchloride
- 2.2. Wall Thickness: 0.010"
- 2.3. Color Code: Brown, White

### 3. Assembly

- 3.1. Nominal Lay Length: 1.25" LHL (9.6 tw/ft)
- 3.2. Separator: Non-Woven Polyester Tape - 100% Coverage

### 4. Jacket

- 4.1. Material: Pressure Extruded Polyvinylchloride
- 4.2. Durometer: 70A
- 4.3. Wall thickness: 0.032"
- 4.4. Diameter: 0.146"
- 4.5. Color: Gray
- 4.6. Ripcord: N/A
- 4.7. Weight: 12 Lbs/Mft

### 5. Markings

- 5.1. Type: Cable permanently identified via surface inkjet print
- 5.2. Legend: LAKE CABLE E206787 26AWG 2C 9U AWM 2464 300V 80°C OR CSA LL226471 AWM I/II A/B 105°C 300V FT1 FT2 FT4 SR "ROHS II" MADE IN USA
- 5.3. Footage Markers: Yes

### 6. Standards

- 6.1. For external interconnection or internal wiring
- 6.2. UL recognized component as type AWM 2464 per UL standard 758
- 6.3. CSA recognized component AWM I/II A/B 105°C 300V per CSA standard 22.2 No. 210-11
- 6.4. All materials used in the manufacturing of this cable are RoHS II and REACH compliant
- 6.5. Maximum Operating Voltage: 300V RMS
- 6.6. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

---

Signature

---

Company

---

Date

**ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION**