



SPECIFICATION OUTLINE

Date: February 24, 2012

Customer: CCT Mexico

Customer P/N: C0979A

Description: Fifteen conductor shielded cable manufactured as UL Type CMG 75°C per NEC Article 800 or UL AWM Style 2464. Also manufactured as CSA type CMG FT4.

Conductors: (15) 22 AWG stranded (7/30) tinned copper conductors.

Insulation: 9 mils minimum average Semi-Rigid PVC.

O.D. over insulation: .049"

Filler: Fibrillated foam polypropylene filler used for roundness.

Shield: Aluminum/polyester tape helically applied over the cable core with the foil side facing out.

Braid Shield: 36 AWG tinned copper applied over the cable core providing 65% coverage.

Jacket nominal wall: 32 mils of PVC.

Color: Gray

Nominal O.D.: .321"

Surface print: "E113422 22 AWG (UL) TYPE CMG 75C OR AWM STYLE 2464 80C 300V --- LL31602 CSA TYPE CMG FT4 75C"

| | | | | | | |
|-------------|---|--------|----|--------------|----|-------------|
| Color code: | 1 | Black | 6 | Blue | 11 | Blue/Black |
| | 2 | White | 7 | White/Black | 12 | Black/White |
| | 3 | Red | 8 | Red/Black | 13 | Red/White |
| | 4 | Green | 9 | Green/Black | 14 | Green/White |
| | 5 | Orange | 10 | Orange/Black | 15 | Blue/White |

Circuit identification on the conductors will be either extruded stripe, spiral ink stripe or landmark at the discretion of EIS Wire & Cable.

Operating temperature: minus 20°C to 80°C

RoHS compliant: Yes

Put-ups: 1,000 FT. +/- 10%

021712 DL