

ALPHA WIRE

Part Number: 16-2251

Issue:

Page 1 of 1 Pages

Issue Date:

7/20/2016

Cable Specification

Component 1 2 PAIR

Conductor: 24 (19/36) AWG TC

Insulation: 0.007" Wall, Nom. MPPE-PE

Color Code: ALPHA WIRE COLOR CODE B

Pair: 2/Cond Cabled Together

Individually Applied:

Shield: FF Foil Tape, 25% Overlap, Min.

Drain Wire: 24 (7/32) AWG TC

Final Assembly 2 Components

Core Wrap: NWP Tape, 25% Overlap, Min.

Shield: AM Foil Tape, 25% Overlap, Min.

Drain Wire: 24 (7/32) AWG TC

Jacket: 0.015" Wall, Nom., MPPE-PE

Jacket OD: 0.185"

Jacket Color: BLACK

Approvals

UL: AWM/STYLE 21460
VW-1

CSA: c(RU) AWM I A/B
FT1

MIL: NONE

CE Compliant: YES

ROHS Compliant: YES

REACH Compliant: NO

Miscellaneous

Temperature: -40 C to 80 C

Voltage: 300 V_{RMS}

Put Ups: 1000 FT PUTUP

Requested Quantity: 3000Ft., 5000Ft.

Application Notes

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.