



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 10/12/2016
Issue: 1

Construction

Description: 2/C 10 105/30 TC PVC/PVC		Diam. (In)
Component:	2 Conductors	
Conductor:	10 AWG 105/30 Tinned Copper to ASTM B-174	0.114"
Insulation:	0.02" PVC Insulated	0.154"
Color Code:	Black, Blue	0.154"
Cable Assembly:	2 Conductors Bunched Cabled	0.308"
Fillers:	Fibrillated polypropylene or solid fillers for roundness (optional)	0.308"
Tape:	Non-Woven Separator Tape for Strip-Ability (optional)	0.311"
Jacket:	0.035" Premium Grade UL PVC	0.381"
Jacket Color:	Gray	0.381"

Print:

Specifications:	AWM Style	Temp	Voltage	Flame	UL List
UL	AWM-20811	105°C	600	VW-1	
Canadian cRU	AWM	105°C	600	FT-1	I/II A/B

Environmental Compliance

- EU Directive 2011/65/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65:

IQ160413



Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372
bhanlon@huesonwire.com

Issue Date: 10/12/2016
Issue: 1

Drawing/Rotation:

IQ160413