



Specification Sheet

Lake Cable Part #: 225CT(26)PU-00

Description: 22 AWG 5 conductor 26 strands tinned copper wire, PVC insulation, unshielded, with an overall TPU jacket.

1. Conductor

- 1.1. AWG Size & Stranding: 22 AWG 26 Strands
- 1.2. Material: Annealed Tinned Copper
- 1.3. Conductor Count: 5 Conductors

2. Insulation

- 2.1. Material: Polyvinylchloride
- 2.2. Wall Thickness: 0.009"
- 2.3. Color Code: Black, Blue, Brown, White, Gray

3. Assembly

- 3.1. Nominal Lay Length: 2.00" LHL (6.00 Tw/Ft)
- 3.2. Binder: N/A
- 3.3. Drain Wire: N/A
- 3.4. Separator: Tissue Wrap - 100% Coverage

4. Jacket

- 4.1. Material: Pressure Extruded Thermoplastic Urethane
- 4.2. Wall Thickness: 0.033"
- 4.3. Diameter: 0.200"
- 4.4. Color: Black
- 4.5. Ripcord: N/A
- 4.6. Weight: 26 Lbs/Mft
- 4.7. Temperature Range: -20°C to +90°C

5. Markings*

- 5.1. Type: Cable shall be permanently identified via surface inkjet print
- 5.2. Legend: TBD
- 5.3. Footage Markers: Yes

6. Standards

- 6.1. All materials used in the manufacture of this cable are RoHS II
- 6.2. Maximum Operating Voltage: 300V RMS
- 6.3. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION

***Client expressly indemnifies Lake Cable, LLC for any liabilities relating in any way to Lake Cable's placement of markings on the product, when such markings are specified for such placement by the client**