


LÜTZE SUPERFLEX® Plus (C) PUR Feedback, Shielded

High Flexing Feedback Cable for Allen-Bradley® and other Systems



LÜTZE SUPERFLEX®
contract



Application

- Incremental encoder cable, termination cable for tachometer, brake sensor, speed sensor
- Full PUR jacket and special TPE cable insulation optimally suited for C-tracks, extremely harsh operating conditions, aggressive coolants and lubricants
- Especially for industrial environments, machines and plants

Characteristics

- High active and passive interference resistance (EMC)
- Special braided shield, optimized for continuous flexing
- Very good alternating bending strength, for continuous flexing
- Low adhesion, abrasion-resistant, nick-resistant, tear-resistant
- Hydrolysis-resistant, microbe-resistant, and rot-resistant
- Resistant to weather, ozone and UV resistant
- Salt water resistant
- Excellent coolant and lubricant resistance
- Resistant to most oils, greases, alcohol-free benzines and kerosene (see tech, information)
- Talc and Silicone free

Technical Data

UL-Approval	AWM 21223
Nominal Voltage	1000V 80°C
Test voltage	3000V
Insulation resistance	Min. 100MΩ x km
Temperature range	Moving -25°C - +80°C Fixed -40°C - +80°C
Minimum bending radius	Moving 10 x cable OD Fixed 6 x cable OD
Burning behavior	Flame retardant per VDE 0482 part 265-2; DIN EN 50265-2 IEC 60332-1 UL 1581 section 1080 VW-1 CSA FT 1
Halogen free	According to DIN EN 50267-2-1

Construction

- Metric conductor
- Bare copper wire super finely stranded per DIN VDE 0295 class 6 and IEC 60228 class 6
- Special TPE conductor insulation
- G: with GNYE ground conductor
x: without ground conductor
- Conductors color-coded for specific system
- Layer pitch optimized
- Fleece wrap over cabled conductors
- Tinned copper braid shield, optical coverage ≥ 85 %
- Extremely oil resistant PUR jacket
- Green jacket RAL 6018

Additional feedback cables for other systems available. Please contact us for further information.

Part No.	Description No. of conductors incl. ground	OD / Ø ca. mm	OD / Ø inches	Weight Lbs/Mft	Copper Lbs/Mft
----------	--	------------------	------------------	-------------------	-------------------

For Allen-Bradley® System and similar

111488	(5x2x0.34) BKWH/BK, RDWH/RD, GNWH/GN, GYWH/GY, OGWH/OG	9.2	0.362	72	36
111489	(2x1.5+2x0.34+6x2x0.14) 1.5: GY, WHGY 0.34: OG, WHOG 0.14: BKWH/BK, RDWH/RD, GNWH/GN, BNWH/BN, YEWY/YE, BUWH/BU	10.8	0.425	121	81