

R5816-620

24AWG SHLD CABLE 15 PRS

#24 AWG OVERALL FOIL SHIELDED CABLE, 15 TWISTED
PAIRS OF 7/32 STRAND TINNED COPPER, .010" PVC
INSULATION, OVERALL ALUMINUM/POLYESTER FOIL SHIELD
WITH DRAIN WIRE, .032" CHROME COLOR MATCHED GRAY
JACKET, .400" NOM. OD., STYLE 2464, 80C, 300V,
VW-1 FLAMMABILITY RATING. * 500 FT. SPOOL MARKED
WITH A-B PURCHASE ORDER & MATERIAL NUMBERS.

(COLOR CODE: WHT/BLU, BLU/WHT; WHT/ORG, ORG/WHT;
WHT/GRN, GRN/WHT; WHT/BRN, BRN/WHT; WHT/GRY, GRY/
WHT; RED/BLU, BLU/RED; RED/ORG, ORG/RED; RED/GRN,
GRN/RED; RED/BRN, BRN/RED; RED/GRY, GRY/RED; BLK/
BLU, BLU/BLK; BLK/ORG, ORG/BLK; BLK/GRN, GRN/BLK;
BLK/BRN, BRN/BLK; BLK/GRY, GRY/BLK.

CHROME PVC JACKET COLOR MATCH:

HUNTER L = 66.75 +-2.5, A2 = -.67 +-1.0

B2 = 2.79 +-1.0

MINIMUM ORDER 2500 FT

STRIPING LAY LENGTH CANNOT EXCEED 3.0 IN (76 MM).

BAND MARKING LAY LENGTH CANNOT EXCEED 1.25 IN
(32MM) REPEAT FOR EACH COLOR.