

854-44368

HellermannTyton

Article Number: 854-44368

Description: Grip Tie, 0.5"x8.0", UL94V-2 Flame Rated, Polyamide; Polypropylene, Maroon, 10/pkg



Base Data	
Local Order Number	GT.50X8MP2V2
Type	GT.50X8
Color	Maroon (MN)
Features and Benefits	<ul style="list-style-type: none"> • UL94V0-2 flame rate material allow use in air handling spaces. • Features quick release for repetitive access to cable and wire. • Can be opened and closed numerous times without failure. • Adjustable so one size can accommodate multiple bundle sizes.
Quantity Per	bag
Product Description	The Grip Tie is a low profile, one piece fastening device. Constructed of polyethylene hook and nylon loop and laminated back to back, the Grip Tie features quick release for repetitive access to cable and wire. Grip Ties are available in a variety of colors and are versatile enough for applications ranging from network installations to bundling power cords.
Short Description	Grip Tie, 0.5"x8.0", UL94V-2 Flame Rated, Polyamide; Polypropylene, Maroon, 10/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	40.0lbs
Minimum Tensile Strength (Metric)	177.93N
Length L (Imperial)	8.0"
Length L (Metric)	203.2mm
Length L2 (Imperial)	1.5"
Length L2 (Metric)	38.1mm
Width W (Imperial)	0.5"
Width W (Metric)	12.7mm
Width W2 (Imperial)	1.0"
Width W2 (Metric)	25.4mm
Bundle Diameter Max. (Imperial)	1.91"
Bundle Diameter Max. (Metric)	48.514mm

854-44368



Material and Specifications		
	Material	Polyamide 6 (PA6)
	Material Shortcut	PP
Logistic and Packaging		
	Package Quantity (Imperial)	10
	Package Quantity (Metric)	10
	Customs Number(Schedule B)	9606100000