

854-44334

# HellermannTyton

Article Number: 854-44334

Description: Grip Tie, 0.5"x12.0", UL94V-2 Flame Rated, Polyamide; Polypropylene, Maroon, 10/pkg



Base Data	
Local Order Number	GT.50X12MP2V2
Type	GT.50X12
Color	Maroon (MN)
Features and Benefits	<ul style="list-style-type: none"> <li>• UL94V0-2 flame rate material allow use in air handling spaces.</li> <li>• Features quick release for repetitive access to cable and wire.</li> <li>• Can be opened and closed numerous times without failure.</li> <li>• Adjustable so one size can accommodate multiple bundle sizes.</li> </ul>
Quantity Per	bag
Product Description	The Grip Tie is a low profile, one piece fastening device. Constructed of a hook and loop design, laminated back to back, the Grip Tie features quick release for repetitive access to cable and wire. Grip Ties are available in a variety of colors and are versatile enough for applications ranging from network installations to bundling power cords.
Short Description	Grip Tie, 0.5"x12.0", UL94V-2 Flame Rated, Polyamide; Polypropylene, Maroon, 10/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	40.0lbs
Minimum Tensile Strength (Metric)	177.93N
Length L (Imperial)	12.0"
Length L (Metric)	304.8mm
Length L2 (Imperial)	1.5"
Length L2 (Metric)	38.1mm
Width W (Imperial)	0.5"
Width W (Metric)	12.7mm
Width W2 (Imperial)	1.0"
Width W2 (Metric)	25.4mm
Bundle Diameter Max. (Imperial)	3.18"
Bundle Diameter Max. (Metric)	80.772mm

854-44334

Material and Specifications		
	Material	Polypropylene (PP)
	Material Shortcut	PA66
Logistic and Packaging		
	Package Quantity (Imperial)	10
	Package Quantity (Metric)	10
	Customs Number(Schedule B)	9606100000