


Description: Six 18 AWG Insulated Conductors,
Overall Polyurethane Jacket

Date: 12/13/16

JM Part Number: JMCCA57779

Reference: 32028638

Cable Assembly



Components Six 18 AWG Insulated Conductors - GXL

Conductors: 18 AWG, 41/34 tinned copper

Insulation: .023" nominal wall of XLPE .093"

Overall Cable

Cabling: Six conductors cabled together around FR PP fillers

Binder: Fleece Tape

Jacket: .080" nominal wall of Pressured Shiny Black PU .438" ± .010"

Print

Unprinted

Color Code

- | | |
|-----------|----------|
| 1. Blue | 4. Black |
| 2. Yellow | 5. White |
| 3. Green | 6. Red |

Alternate Color Code (For First Cable Run Only)

- | | |
|-----------|----------|
| 1. Violet | 4. Black |
| 2. Yellow | 5. White |
| 3. Gray | 6. Brown |

Coil Requirements

Nom Retracted Coil Length: 8" ± 1"

Nominal Coil Diameter: 1.380"

Tail 1 Length: 12 1/4" ± 1" (9 3/4" ± 1" stripped)

Tail 2 Length: 12 1/4" ± 1" (9 3/4" ± 1" stripped)

Requirements

Temperature: -45C to 90C

Voltage: 300V

Written By:	scs/ad/ra	12/13/2016	Rev. 0	Initial Issue
Revised By:	scs	12/19/2016	Rev. 1	Change JM P/N From JMCCA57777 to JMCCA57779, Added FR PP Fillers to cabling
Revised By:	scs	1/25/2017	Rev. 2	Chg Tail Lengths from 15 to 12 1/4", Chg Stripped Lengths from 9.25 to 9 3/4"; Add Shiny to Jkt
Revised By:				