



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: info@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

28-Nov-2013

Product Number : **5152204TFT4.1**

RoHS

O/A SH CABLE 4/C 22/7 AWG STC
SR-PVC Insulation
PVC FT-4 Jacket

Conductor : 22 AWG 7 Strand STC Cond	
Total Cable Weight : 47 kg/km	Final Diameter : 0.216 inches
Insulation : SR-PVC	Jacket : PVC
Shield : Foil Shield	
Drain : 24 AWG 7 Strand STC Cond.	
DC Resistance 25°C: 16.7 Ohms / 1000 ft	Mutual Capacitance : 36.2 pF/ft
Impedance : 60 Ohms	Cond to Shield Cap. : 65.4 pF/ft
Velocity of Prop : 64 %	Inductance. : 1.3 mH/km

Print Notes :

Standard Print : ECI CSA CMG 105°C OR AWM II A/B 105°C LL61365 300V FT-4 RU AWM
E107863 STYLE 2464 300V VW-1 22 AWG RoHS

(All of the above values are approximated to within 10%)