



Hueson Wire  
 38 Sutton Street  
 Northbridge, MA 01534  
 508-234-6372  
[bhanlon@huesonwire.com](mailto:bhanlon@huesonwire.com)

**Issue Date:** 7/1/2016  
**Issue:** 1

**Construction**

<b>Description:</b> 2/C 24 19/34 TC mPPE/PVC		<b>Diam. (In)</b>
<b>Component:</b>	2 Conductors	
<b>Conductor:</b>	24 AWG 19/36 Tinned Copper to ASTM B-8	0.024"
<b>Insulation:</b>	0.007" mPPE UL Approved	0.038"
<b>Color Code:</b>	Black, Red, Green	0.038"
<b>Cable Assembly:</b>	2 Conductors Bunched Cabled	0.076"
<b>Fillers</b>	Fibrillated polypropylene or solid fillers for roundness (optional)	0.076"
<b>Drain Wire:</b>	No Drain	0.076"
<b>Shield:</b>	Aluminum Mylar Foil Shield	0.079"
<b>Tape:</b>	Non-Woven Separator Tape for Strip-Ability (optional)	0.079"
<b>Braid:</b>	Tinned Copper Braid Shield	0.079"
<b>Jacket:</b>	0.015" mPPE Polyphnyylene	0.109"
<b>Jacket Color:</b>	Gray	0.109"

Print:

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>	<u>UL List</u>	
<b>UL</b>	AWM-2464	80°C	300	VW-1	CM	
Canadian cRU	AWM	80°C	300	FT-1	CMG	I/II A/B

**Environmental Compliance**

- EU Directive 2011/95/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65:

IQ160278