CHEMINAX

12-6-05 120 OHM, 0.8mm², 19 STRANDS, Date: TWIN CONDUCTOR CABLE, J1939-15 COMPLIANT Revision: Е

THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.

CONSTRUCTION DETAILS


ELECTRICAL CHARACTERISTICS

DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE DESIGNATED.

CHARACTERISTIC IMPEDANCE 120 ± 12 ohms, Method D at 1 MHz

CAPACITANCE 10.5 pF/ft. (nominal) at 1 MHz

VELOCITY OF PROPAGATION 67% (nominal)



CONDUCTORS

AWG 19, 19 Strands of 0.23 mm, Bare Copper

ADDITIONAL REQUIREMENTS

DIELECTRICS

Rayfoam® M Colors - Yellow/Green

ELECTRICAL

CONDUCTORRESISTANCE **INSULATION RESISTANCE**

7.74 ohms/1000 ft. (nominal) 10,000 megohms (minimum)

for 1000 ft.

VOLTAGE WITHSTAND

1000 volts (rms) (minimum)

(DIELECTRIC)

ENVIRONMENTAL

FLAMMABILITY Method C **HEATSHOCK** 225°C

LOWTEMPERATURE--55°C/6.00 inch mandrel

COLD BEND

VOLTAGE WITHSTAND

(POSTENVIRONEMENTAL)

1000 volts (rms), 1 minute



PHYSICAL

CONCENTRICITY

DIELECTRIC

(PRIOR TO CABLING)

ELONGATION 150%(minimum) **TENSILE STRENGTH** 1500 lbf/in² (minimum)

JACKET

ELONGATION TENSILE STRENGTH JACKETTHICKNESS

300%(minimum) 2500 lbf/in2 (minimum)

70%(minimum)

 $.030 \pm .005$ inch

LAY LENGTH $1.3 \pm .2$ inch

Outer jacket will be black (designated by a "-0" appended to the part number, e.g., 2019E0309-0) unless otherwise specified.

JACKET MARK: Mark outer jacket at 12 inch (nominal) intervals in white ink as follows:

Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.

for product jacketed in USA "RAYCHEM SAE J1939-15 0.8mm2" for product jacketed in Mexico "RAYCHEM SAE J1939/15 0.8mm2"

WEIGHT 23.5 lbs/1000 ft. (nominal)

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.

Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.



209

(minimum)

.228

(nominal)

