

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Spec ID: 5/C- 1020
Spec Revision Level: A7

Description: (5) Conductor Round Cable with 2 / 18 Ga SXL , 1/ 12 Ga SXL, 1/ 10 Ga SXL & 1/ 8 Ga SXL Inners,105 DegC PVC Jacket

Inners: SXL-18-16-B (LBL) / SXL-18-16-B (LBL / RED) / SXL-12-19-B (RED) / SXL-10-19-B (YEL) / SXL-8-19-B (ORG)
All Inners are XLPE Insulated, 125C rated

Finished Cable:

Cable Lay : 5.0 inches
Outer Jacket: PVC 105 Deg C, Lead Free Compound
Outer Jacket Color: Orange (Tubed Jacket)
Jacket Wall Thick (Min): 0.040 inches
Jacket Wall Thick(Nom): 0.050 inches
Jacket Max OD : 0.575 inches
Jacket Nom OD : 0.570 inches
Jacket Min OD : 0.565 inches
Separator : One 1 3/4" Paper
Filler: Six Fillers
Max Runout: 0.012 inches
Surface Print: None

Specification Reference Data

SAE: J-1128(Rev Dec, 2015)	Ford: N/A	Chrysler: N/A
UL : N/A	CSA: N/A	Packard: N/A
Other: N/A		

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By:

Mir Hussain (Corporate Quality Engineer)

Date: 1-16-2017