

115-06200

Article Number: 115-06200

Description: Releasable Cable Tie, 8.5" Long, 40 lb Tensile Strength, PA66, Black, 100/pkg



| Base Data                           |  |
|-------------------------------------|--|
| Local Order Number                  | RT40R0C2   |
| Type                                | RT40R  |
| Color                               | Black (BK)   |
| Features and Benefits               | <ul style="list-style-type: none"> <li>• Special design offers a release feature for quick and easy access to wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force even after repeated use.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>  |
| Quantity Per                        | bag  |
| Product Description                 | HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force . For high volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Short Description                   | Releasable Cable Tie, 8.5" Long, 40 lb Tensile Strength, PA66, Black, 100/pkg  |
| Product Dimensions                  |  |
| Minimum Tensile Strength (Imperial) | 40.0lbs  |
| Minimum Tensile Strength (Metric)   | 180.0N   |
| Length L (Imperial)                 | 8.5"   |
| Length L (Metric)                   | 215.0mm  |
| Fixation Method                     | None   |
| Identification Plate Position       | none   |
| Releasable Closure                  | Yes  |
| Tie Closure                         | plastic pawl   |
| Variant                             | Inside Serrated  |
| Width W (Imperial)                  | 0.16"  |
| Width W (Metric)                    | 4.0mm  |
| Bundle Diameter Min. (Imperial)     | 0.06"  |
| Bundle Diameter Min. (Metric)       | 1.5mm  |

115-06200



|                             |                                 |                                  |
|-----------------------------|---------------------------------|----------------------------------|
| Product Dimensions          | Bundle Diameter Max. (Imperial) | 2.0"                             |
|                             | Bundle Diameter Max. (Metric)   | 51.0mm                           |
| Material and Specifications |                                 |                                  |
|                             | Material                        | Polyamide 6.6 (PA66)             |
|                             | Material Shortcut               | PA66                             |
|                             | Flammability                    | UL94 V2                          |
|                             | Minimum Application Temperature | -                                |
|                             | Operating Temperature           | -40°F to +185°F (-40°C to +85°C) |
|                             | ROHS Compliant                  | Yes                              |
|                             | Certification/Specification     | UL                               |
|                             | UL Recognized (US and Canada)   | Yes                              |
| Logistic and Packaging      |                                 |                                  |
|                             | Package Quantity (Metric)       | 100                              |
|                             | Customs Number(Schedule B)      | 3926909987                       |