



**Description:** Two 22 AWG Conductors  
 Overall Braid and  
 PU Jacket

**Date:** 2/17/2017

**JM Part Number:** TBD  
**Reference:** TBD

**Components** Two 22 AWG Insulated Conductors

Conductor: 22 AWG, 19/34 tinned copper

Insulation: .010" nominal wall of FEP (See Color Code) .050"

**Cable Construction**

Cabling: Two conductors cabled together with FR PP Fillers

Binder: Fleece tape

Drain Wire: 24 AWG, 19/36 tinned copper

Braid Shield: 36 AWG tinned copper braid, 90% coverage

Separator: Tissue tape

Jacket: .035" nominal wall of Pressured Matte Black Polyurethane .190"  
 (Estane 58202)

**Print (White Inkjet)**

E66440 2/C 22 AWG SHIELDED AWM 20668 90C 300V OR   
 AWM I/II A/B 90C 300V FT1

**Color Code**

1. Red 2. Blue

**Requirements**

Temperature: 90C  
 Voltage: 300V

Voltage: UL AWM Style 20668  
 AWM FT1  
 Materials are RoHS Compliant  
 (2011/65/EU & EU 2015/863)

Written By:	scs	2/17/2017	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				