

32032823



TE Wire & Cable

The most trusted name in thermocouple wire since 1941

107 North First Street • Suite B-204 • NJ 07624-4197 • 888-415-4462 • www.tewc.com

PRODUCT SPECIFICATION: QW19208			
20 AWG, 5-pair, type JX, PVC ins., overall shield, PVC jkt. ANSI color code.			
DRAWN: M. PETERS	3/10/2017	REVISION	APPROVED BY
CHECKED:			DATE
CUSTOMER APP.:			

Manufacturing description: UP/ALPTWK-05-20F-JX SP PRINT

Construction Details

Conductor 20 AWG, stranded thermocouple, extension grade, type JX per ASTM E230 & ANSI MC96.1

Insulation Extruded PVC. Nominal Diameter: .068".
Color Code: (+) White, (-) Red

Twisting of pairs Conductors are twisted together.
One conductor in each pair is number printed for identification.

Cabling (5) pairs are cabled together and shielded with a drain.
Shield - Aluminum/Polyester tape applied helically.
Drain - 20 AWG stranded tin plated copper wire.

Jacket Extruded PVC. Nominal Final Diameter: .448".
Color: Black.

Other Subject UL 13, Type PLTC
Rated 105°C, 300V

Print Legend: ENOKABLE EK78027-JX-F STRANDED THERMOCOUPLE CABLE ES4438 "T" (UL)
TYPE PLTC/ITC 105°C 20 AWG 5 PAIR THCP L EXTN TYPE JX

The information contained in this drawing is proprietary property of TE Wire & Cable. It may not be used or reproduced, in whole or in part, without written authorization of TE Wire & Cable