

Specification

Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
 www.huesonwire.com

Issue Date: 12/15/17

Issue: 1

Construction C-5528 Dimmer Cable

Description: 5/C Comp 3/C 18 41/34 + 2/C 22 26/36BC Dimmer Cable		Diam. (In)
Components:	5 Total conductors	
Conductor 1:	3 Conductors 18 AWG 41/34 Bare Copper to ASTM B-174	0.048 "
Insulation:	0.015" Premium Grade PVC	0.078 "
Color Code	Green, Black, White	0.078 "
Conductor 2:	2 Conductors 22 AWG 26/36 Bare Copper to ASTM B-174	0.030 "
Insulation:	0.015" Premium Grade PVC	0.060 "
Color Code	Gray + Violet	0.060 "
Cable Assembly:	Bunch Cable 3/C 18 AWG with 2/C 22 AWG	0.190 "
Tape:	Non-Woven Separator Tape for Strip-Ability (Optional)	0.194 "
Jacket:	0.038" AWM Jacket Compound	0.270 "
Jacket Color:	Black or White	0.270 "
Print:	E174416 RU AWM 20811 105C 600V OR 2661 105C 300V VW-1 --- cRU AWM I/II A 105C 600V FT-1	

C5528-B

Environmental Compliance

- **RoHS EU Directive 2011/65/EU (1&2)**


All materials used in the manufacture of this part are in compliance with EU Directive 2011/65/EU (1 & 2) regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

- **REACH Regulation 169:**

This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

- **California Prop 65:**

The outer surface of materials used to manufacture this part meet requirements of California Prop. 65



Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372
www.huesonwire.com

Issue Date: 12/15/2017

Issue: 1

Construction

