Hues Wire & Cal	Specification	Hueson Wire 38 Sutton Street Northbridge, MA 01534 508-234-6372 www.huesonwire.com Issue Date: 12/15/17	-	
Construct	tion C-5528 Dimme	r Cable	1	
Description	: 5/C Comp 3/C 18 41/34 + 2/C 22 26/36BC Dir	nmer Cable Dia	m. (In)	
Components:	5 Total conductors			
Conductor 1:	3 Conductors 18 AWG 41/34 Bare Cop	per to ASTM B-174	0.048 "	
Insulation:	0.015" Premium Grade PVC		0.078 "	
Color Code	Green, Black, White		0.078 "	
Conductor 2:	2 Conductors 22 AWG 26/36 Bare Cop	per to ASTM B-174	0.030 "	
Insulation:	0.015" Premium Grade PVC		0.060 "	
Color Code	Gray + Violet		0.060 "	
Cable Assembly:	Bunch Cable 3/C 18 AWG with 2/C 22 AWG		0.190 "	
Tape:	Non-Woven Separator Tape for Strip-Ability (Op	tional)	0.194 "	
Jacket: Jacket Color:	0.038" AWM Jacket Compound Black or White		0.270 "	
Jackel Color.	Black of White		0.270 "	
Print:	rint: E174416 RU AWM 20811 105C 600V OR 2661 105C 300V VW-1 cRU AWM I/II A 105C 600V FT-1			
Environmental (	Compliance	C5	528-B	
	compliance ctive 2011/65/EU (1&2)			
All materials used in the manufacture of this part are in compliance with EU Directive 2011/65/EU (1 & 2) regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.				
	ation 169: This product does not contain Substances of Very High REACH candidate list in excess of 0.1% mass of the iter			
California Prop	o 65:			
	The outer surface of materials used to manufacture this	part meet requirements of California Prop. 65		

