

N13-44B+00068-9UL
Customer P/N: 32033419

4 CONDUCTOR CABLE

90 OHM REFERENCE TWINAX (1)UL AWM 10860 26 AWG
INSULATED SINGLES (2)26 AWG 66/44 BARE COPPER, 0.008"
PFA TO 0.035" +/- 0.002" OD-WHITE, GREEN UL AWM 10860

CABLE 26 AWG SINGLES (2) 0.069" +/- 0.004" OD

UL AWM 10860 26 AWG INSULATED SINGLES (2) 26 AWG 66/44
BARE COPPER, 0.0065" (0.0055" MIN) PFA TO 0.032" +/-
0.002" OD-RED, BLACK UL AWM 10860

CABLE 90 OHM REFERENCE TWINAX (1) 26 AWG SINGLES (2)
FILLER: LSNW POLYESTER IN THE INTERSTICES

BRAID 44 AWG TINNED COPPER 90.0% MIN COVERAGE

INSULATE 0.033" (0.030" MIN) SILICONE RUBBER JACKET TO
0.177" +/- 0.006" OD-GRAY TO UL AWM 4515 150C 300V

MINIMUM = 1,000 FEET

FINISHED WEIGHT = (16.56#/KFT) (0.0246KG/MTR)

Spool Size: 18" PLYWOOD-B

RoHS Compliant 2002/95/EC & 2011/65/EU

This product is NAFTA eligible.