


PRODUCT SPECIFICATION

<i>DATE</i>	<i>REV</i>	<i>ECN</i>	<i>DESCRIPTION</i>
10/22/2012	A	E22804	SPECIFICATION CREATED

Parent Number: F16415-

Description: 16 26/30 TC AWM 3289/3321/3505 or 3271 or 3320 VW-1 CL1503 or AWM I A

DIAMETER: 0.119
TOLERANCE ± : 0.003



0.030

MINIMUM WALL: 0.027

Stranding: 26/30 TC

Style: UL: AWM 3271/3289/3320/3321/3505 CSA: CL1503 or AWM I A

Insulation: XLPE

Print Legend: 16 AWG (1.31mm²) E96824 (PLANT ID CODE) (AWM LOGO) AWM 3289/3321/3505 150C or 3271 125C or 3320 90C 600V AC 750V DC VW-1 -- 156016 CSA CL1503 150C 600V or AWM I A 150C 600V FT1 -- MADE IN USA

Voltage: UL=600Vac 750Vdc

Temperature: 3289/3321/3505=150C, 3271=125C, 3320=90C

Notes:

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Approval:

Customer Part Nbr(s): _____

Approved By: _____ **Date:** _____

Title: _____ **Company Name:** _____

COLEMAN CABLE, INC

1530 Shields Drive
Waukegan, IL 60085

Phone: 1-800-323-9355

www.colemancable.com

