



Coast™ Custom Cable

(310) 639-9473 Phone (310) 763-2225 Fax
Distributor Name: **IEWC**
End Use Customer: **Auris Surgical Robotics**
IP Owner: **Auris Surgical Robotics**

Part Number: **17-1172 __199**

Revision: **None**

Customer P/N: **N/A**

Customer Revision: **None**

Lead Wire Specification

28 AWG Lead Wire

CONDUCTOR

Wire Size & Type: 28 AWG (40X44) Tinned Copper
Nom. Wire Diameter: 0.015

INSULATION

Insulation Type: FEP
Nom. Ins Thickness: 0.005
Lead Wire Diameter: **0.025**
Tolerance (+/-): 0.002

COLOR	PART NUMBER
Black	17-1172 BK199
Brown	17-1172 BR199
Red	17-1172 RD199
Orange	17-1172 OR199
Yellow	17-1172 YL199
Green	17-1172 GR199
Blue	17-1172 BL199
Violet	17-1172 V1199
Gray	17-1172 SL199
White	17-1172 WH199

TESTS

Test 1: Physical/Dimensional
Test 2: Spark - 4000VAC

MISCELLANEOUS

Voltage: 150V
Temperature: -50°C to +80°C
Put Ups: Bulk, May Contain Multiple Lengths Per Reel
Reel: Wood or Plastic
Print: None
Colors: Munsell® Component Limits of Deviation

ENVIRONMENTAL

RoHS Directive: European Directive 2011/65/EU

APPROVALS

Final Product: None



UNCONTROLLED
COPY

Dimensions in inches unless otherwise specified

.XXX = +/- .005 .XX = +/- .02 .X = +/- .1

UNCONTROLLED COPY

Prepared By: Jason Kovaric

Customer Approval: _____

Date: 2/21/2017

Title: _____

Configuration Code: 2511912

Date: _____

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.