		DATE	REV	ECN	DESCRIPTION
PRODUCT	SPECIFICATION	8/7/2017	С		Added the DIN 76722 designation.
INODUCIA	<u>SI LEITIEATION</u>				
Parent Number:	FMK008-				
Description	1.5mm2 19/.31mm BC TW 3TAD ES-AU5T-	<u>0.091</u>			$\checkmark$
Description.	1A348-AA Ford Global Spec FLRYW-A ISO TOLERANCE ± :	<u>0.004</u>			
	<u>6722-1</u>				
				/ 688	
<u>Stranding:</u>	<u>19/.31mm BC LHL</u>		▼		NOM WALL: 0.012
Style	Ford: ES-AU5T-1A348-AA 3TAD; ISO 6722-1; DIN 76722 FLRY				MINIMUM WALL: 0.009
51/10.	1.5-A T125; FLRYW-A				$\mathbf{MINIMUM WALL: } \underline{0.009}$
Insulation:	<u>125C PVC</u>				
<u>Print Legend:</u>					
Voltage: Nominal system voltage of 60 V rms or less in automotive electrical harnesses.					
<i>Temperature:</i> <u>-40C to +125C</u>					
<u>1 emperature:</u>	-400 10 +1250				
Notes:					
This product complies with European Directive 2011/65/EU (RoHS 2)					
The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order					
subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.					
This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed					
to any party without written consent of Southwire Company, LLC.					~ ~ 1 1 <sup>®</sup>
<u>Customer Approval:</u>					Copperfield
Customer Part Nbr(s):				113	5 W. North Street
Approved By:Date:					rs w. North Street emen, IN 46506
Title:	Company Name:				one: 1-574-546-5115