

32035391



TE Wire & Cable

The most trusted name in thermocouple wire since 1941

107 North Elm Street • South Bend, IN 46704-0109 • 888-4TE-WIRE • WWW.TEWANDC.COM

PRODUCT SPECIFICATION: QW19215

20 AWG, 8-pair, type JX, PVC Ins, overall shield, PVC jkt. ANSI color code.

DRAWN: M. PETERS

3/10/2017

REVISION

APPROVED BY

DATE

CHECKED:

CUSTOMER APP.:

Manufacturing description: UP/ALPTWK-08-20-JX SP PRINT

Construction Details

Conductor 20 AWG, solid thermocouple, extension grade, type JX per ASTM E230 & ANSI MC96.1

Insulation Extruded PVC. Nominal Diameter: .068".
Color Code: (+) White, (-) Red

Twisting of pairs Conductors are twisted together.
One conductor in each pair is number printed for identification.

Cabling (8) pairs are cabled together and shielded with a drain.
Shield - Aluminum/Polyester tape applied helically.
Drain - 20 AWG stranded tin plated copper wire.

Jacket Extruded PVC. Nominal Final Diameter: .480".
Color: Black.

Other Subject UL 13, Type PLTC
Rated 105°C, 300V

Print Legend: ENOKABLE EK78019-JX SOLID THERMOCOUPLE CABLE E54438 "T" (UL)
TYPE PLTC/ITC 105°C 20 AWG 8 PAIR THCP L EXTN TYPE JX

The information contained in this drawing is proprietary property of TE Wire & Cable. It may not be used or reproduced, in whole or in part, without written authorization of TE Wire & Cable