

32035392



TE Wire & Cable

The most trusted name in thermocouple wire since 1944
107 North 7th Street • Spring Brook, NJ 07081-6167 • 908-475-7100 • www.tew-cable.com

PRODUCT SPECIFICATION: QW19210

20 AWG, 12-pair, type JX, PVC Ins, overall shield, PVC Jkt. ANSI color code:

DRAWN: M. PETERS 3/13/2017

CHECKED: _____ REVISION _____ APPROVED BY _____ DATE _____

CUSTOMER APP.:

Manufacturing description: UP/ALPTWK-12-20F-JX SP PRINT

Construction Details

Conductor 20 AWG, stranded thermocouple, extension grade, type JX per ASTM E230 & ANSI MC96.1

Insulation Extruded PVC. Nominal Diameter: .068".
Color Code: (+) White, (-) Red

Twisting of pairs Conductors are twisted together.
One conductor in each pair is number printed for identification.

Cabling (12) pairs are cabled together and shielded with a drain.
Shield - Aluminum/Polyester tape applied helically.
Drain - 20 AWG stranded tin plated copper wire.

Jacket Extruded PVC. Nominal Final Diameter: .584".
Color: Black.

Other Subject UL 13, Type PLTC
Rated 105°C, 300V
Print Legend:

ENOKABLE EK78020-JX-F STRANDED THERMOCOUPLE CABLE ES4438 "T" (UL)
TYPE PLTC/ITC 105°C 20 AWG 12 PAIR THCP L EXTN TYPE JX

The information contained in this drawing is proprietary property of TE Wire & Cable. It may not be used or reproduced, in whole or in part, without written authorization of TE Wire & Cable