



Single 600-J / -O

special single core cable, 600 V, meter marking



HELUKABEL Single 600-J 1G16mm² E 170315 AWM STYLE 10107 90°C 600V VW1 c9A AWM I/II A/B 90°C 600V FT1 CE



HELUKABEL Single 600-O 1x16mm² E 170315 AWM STYLE 10107 90°C 600V VW1 c9A AWM I/II A/B 90°C 600V FT1 CE

Technical data

- Special PVC single core acc. to UL Style 10107 and CSA AWM I/II A/B, adapted to DIN VDE 0285-525-2-31 / DIN EN 50525-2-31, DIN VDE 0285-525-2-51 / DIN EN 50525-2-51, acc. to UL Std.758
- **Temperature range**
flexing -5°C bis +90°C
fixed installation -40°C bis +90°C
- Permissible conductor **operating temperature** +90°C
- **Nominal voltage**
VDE U₀/U 600/1000 V
UL/CSA 600 V
- **Test voltage**
4000 V
- **Breakdown voltage**
min. 8000 V
- **Minimum bending radius**
flexing 7,5x cable Ø
fixed installation 4x cable Ø
- **Radiation resistance**
up to 80x10⁶ cJ/kg (up to 80 Mrad)

Cable structure

- Bare copper, fine wire conductors to DIN VDE 0295 cl.5, BS 6360 cl.5 and IEC 60228 cl.5
- Core insulation of special PVC to class 43, 90°C acc. to UL Std.1581 colour black or green-yellow
- Outer sheath of special PVC compound type TM2 to DIN VDE 0207-363-4-1 / DIN EN 50363-4-1 and class 43 acc. to UL Std.1581
- Sheath colour: black (RAL 9005)
- With meter marking

Properties

- Chemical Resistance see "Technical Informations"
- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers
- UV resistant

Tests

- PVC self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1-2 (equivalent DIN VDE 0472 part 804 test method B), UL VW-1, CSA FT1

Note

- G = green-yellow
x = black
- AWG sizes are approximate equivalent values. The actual cross section is in mm².
- Screened analogue type:
Single 600-CY-J / -O
- Also as 1000 V Style 10678 deliverable

Application

PVC Single cores suitable for installation for flexible use for medium mechanical stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms as well as outside (fixed installation). Is not suitable to be used as direct burial- or as underwater cable. These two norms approved single cores designed for exportorientated machinery manufacturer for machine tools, conveyor belts and production lines.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no.	No. cores x cross-sec. mm ²	AWG-No.	Core colour	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
10881	1 G 6	10	green-yellow	7,8	58,0	118,0
10882	1 x 6	10	black	7,8	58,0	118,0
10883	1 G 10	8	green-yellow	9,0	96,0	180,0
10884	1 x 10	8	black	9,0	96,0	180,0
10885	1 G 16	6	green-yellow	10,0	154,0	250,0
10886	1 x 16	6	black	10,0	154,0	250,0
10887	1 G 25	4	green-yellow	11,5	240,0	370,0
10888	1 x 25	4	black	11,5	240,0	370,0
10889	1 G 35	2	green-yellow	13,0	336,0	490,0
10890	1 x 35	2	black	13,0	336,0	490,0
10891	1 G 50	1	green-yellow	15,6	480,0	665,0
10892	1 x 50	1	black	15,6	480,0	665,0

Part no.	No. cores x cross-sec. mm ²	AWG-No.	Core colour	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
10893	1 G 70	2/0	green-yellow	17,9	672,0	910,0
10894	1 x 70	2/0	black	17,9	672,0	910,0
10895	1 G 95	3/0	green-yellow	19,5	912,0	1195,0
10896	1 x 95	3/0	black	19,5	912,0	1195,0
10897	1 G 120	4/0	green-yellow	22,3	1152,0	1545,0
10898	1 x 120	4/0	black	22,3	1152,0	1545,0
10899	1 G 150	250 kcmil	green-yellow	25,0	1440,0	1750,0
10900	1 x 150	250 kcmil	black	25,0	1440,0	1750,0
10901	1 G 185	350 kcmil	green-yellow	28,6	1776,0	2320,0
10902	1 x 185	350 kcmil	black	28,6	1776,0	2320,0
10903	1 G 240	450 kcmil	green-yellow	31,4	2304,0	2960,0
10904	1 x 240	450 kcmil	black	31,4	2304,0	2960,0

Dimensions and specifications may be changed without prior notice. (RN06)