



# SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896  
Fax: 613-394-4101 email: info@electrocables.com  
Mailing: P.O. Box 276, Trenton, ON K8V 5R5  
www.electrocables.com

27-May-2015

Product Number : **5152204TFT4**

**RoHS**

**O/A SH CABLE 4/C 22/7 AWG STC  
SR-PVC Insulation  
PVC FT-4 Jacket**

Conductor : 22 AWG 7 Strand STC Cond.	
Total Cable Weight : 29 kg/km	Final Diameter : 0.163 inches
Insulation : SR-PVC	Jacket : PVC
Shield : Foil Shield 0.5	
Drain: 24 AWG 7 Strand STC Cond.	
DC Resistance 25°C: 15.7 Ohms /1000 ft	Mutual Capacitance : 36 pF /ft
Impedance : 60 Ohms	Cond to Shield Cap. : 65 pF /ft
Velocity of Prop : 64 %	Inductance. : 1.5 mH/km

Print Notes :

Standard Print: ECI ELECTROCOM CSA CMG 105°C LL61365 OR CSA AWM II A/B 105°C  
600V FT-4 (UL) CMG E 132883 105°C #22 AWG RoHS

( All of the above values are approximated to within +/- 10% )

5152204TFT4