

MULTICONDUCTOR CABLE



MULTICONDUCTOR BRAIDED SHIELD

105°C- 300V

Description:

Each Conductor Stranded Tinned Copper, Color Coded Polyvinylchloride Insulated, Tinned Copper Braided Shield, Gray PVC Jacket Overall

Specifications:

UL Listed, NEC Type CM or CL2, 75°C

UL AWM Style 2095, 80°C, 300V

CSA Certified PCC FT-4

WEICO NO.	NO. OF COND.	CONDUCTOR		NOM. JACKET THICKNESS (INCHES)	UL NEC RATING	NOM. O.D. (IN)
		AWG	STRAND			
Insulation Thickness .016"						
9450 *	1	22	7/30	.020		.120
9451	2	22	7/30	.020	CM	.180
9452	3	22	7/30	.020	CM	.200
9453	4	22	7/30	.020	CM	.210
9454 *	1	20	10/30	.020		.130
9455	2	20	10/30	.020	CL2	.200
9456	3	20	10/30	.020	CL2	.220
9457	4	20	10/30	.020	CL2	.230
9458 *	1	18	16/30	.020		.140
9459	2	18	16/30	.020	CM	.230

WEICO NO.	NO. OF COND.	CONDUCTOR		NOM. JACKET THICKNESS (INCHES)	UL NEC RATING	NOM. O.D. (IN)
		AWG	STRAND			
9460	3	18	16/30	.020	CM	.240
9461	4	18	16/30	.020	CM	.250
9462	2	16	26/30	.020	CL2	.250
9463	3	16	26/30	.020	CL2	.250

*Single Conductor Cables UL AWM Style 1108, 80°C, 300V, VW-1

Standard Put-Ups: 100 ft., 500 ft., 1000 ft.