



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: info@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

6-Aug-2014

Product Number : 5152004TFT4

RoHS

**O/A SH CABLE 4/C 20/7 AWG STC
SR-PVC Insulation
PVC FT-4 Jacket**

Conductor : 20 AWG 7 STC Conductor	
Total Cable Weight : 42 kg/km	Final Diameter : 0.210 inches
Insulation : SR-PVC	Jacket : PVC
Shield : Foil Shield 0.625	
Drain : 24 AWG 7 STC	
DC Resistance 25°C: 10.3 Ohms / 1000 ft	Mutual Capacitance : 38.1 pF/ft
Impedance : 55 Ohms	Cond to Shield Cap. : 68.3 pF/ft
Velocity of Prop : 65 %	Inductance. : 1.3 mH/km

Print Notes :

Standard Print : ECI ELECTROCOM CSA CMG 105°C LL61365 OR CSA AWM II A/B 105°C
600V FT-4 (UL) CMG E132883 105°C #20 AWG RoHS

UL AWM/STYLE 2464 AVAILABLE UPON REQUEST
TEMPERATURE RANGE: -30°C to 105°C

(All of the above values are approximated to within +/- 10%)

5152004TFT4