

**1. CONDUCTOR:**

- 1.1 Size and Material: 20 7/.0121" AWG nickel-plated copper wire.
- 1.2 O.D.: .036" nom.

**2. INSULATION:**

- 2.1 Extruded PTFE.
- 2.2 Print on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .076" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 250°C




**4. REFERENCE:**

- 4.1 UL Subject 758 (AWM), Style 1659.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.								 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: <i>Pierre Garand</i>		 <p>1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourtd.com</p>				
1512									Date: January 25, 2008						
									Verified: <i>David L...</i>						
									Date: January 25, 2008		Description: <b>XE20N207/0121-X</b>				
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.									 <p>A member of The Marmon Group of companies</p>		Size: <b>A</b>	Scale: ---	Page: 1 of 1	Code Ident. No: <b>57104</b>	Specification No.: <b>F02049-X</b>