

1. CONDUCTOR:

- 1.1 Size and Material: 18 AWG, 19 strands, nickel-plated copper wire.
- 1.2 O.D.: .044" nom.

2. INSULATION:

- 2.1 Extruded PFA.
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .064" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 250°C




4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 10362.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I, Group A/B.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.								 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: <i>Pierre Barand</i> Date: August 26, 2008		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourtd.com					
1396	1569								Verified: <i>David L...</i> Date: August 27, 2008		Description: XPA10N1819/0092-X					
UNCONTROLLED DOCUMENT									Size: A Scale: --- Page: 1 of 1		Code Ident. No: 57104		Specification No.: F04471-X		Rev. B	
A later revision of this specification may exist.									 A member of The Marmon Group of companies							
Wire & Cable Specification - HBR.04.86.D																