



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: sales@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

23-Feb-2017

Product Number : 9000241BUV

RoHS

Composite Trailer Cable
6/c 12/65 Stranded Bare Copper Conductor &
1/c 10/105 Stranded Bare Copper Conductor
PVC Insulation
PVC Jacket
Operating Temperature: -65°C to 85°C

General Specification of Product :

Final Diameter :	0.533 inches	13.538 mm
Total Cable Weight:	382 kg/km	257 lbs/1000 ft
Conductor :	6/C 12/65 SBC & 1/C 10/105 SBC	
Insulation :	PVC	
Outer Jacket :	PVC	

Print Notes :

Standard Print : TRUCK/TRAILER CABLE 6/C 12 AWG 1/C 10 AWG -65°C/-85°F RoHS

Additional Information :

UNSH 6/C 12/65 SBC
DC Resistance: 25°C 1.6 Ohms/1000'
Mutual Capacitance: 35 pF/ft
Impedance: 65 Ohms
Velocity of Prop: 62%
Inductance: 1.2 (mH/km)

Unsh 2/C 18/16
DC Resistance: 25°C 1.1 Ohms/1000'

Please contact Sales regarding Finished Lengths, Insulation and Jacket Colours.

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 30 years.

(All of the above values are approximated to within +/- 10%

9000241BUV