



1375191-2

**SL 110 Series Modular jack, RJ45, Category 5e, unshielded, without dust cover**

## Body Features

110 Block Material Polycarbonate

## Configuration Features

Keyed No  
Number of Positions 8  
Wiring Pattern Universal

## Contact Features

Contact Base Material Beryllium copper  
Contact Mating Area Plating Material Gold  
Contact Mating Area Plating Thickness 50.00  $\mu\text{in}$  | 1.27  $\mu\text{m}$

## Dimensions

Insulated Conductor Outside Diameter 0.057 in | 1.45 mm  
Solid Wire Range .51 mm<sup>2</sup> | .65 mm<sup>2</sup>  
Stranded Wire Range .14 mm<sup>2</sup> | .2 mm<sup>2</sup>  
Wire Range 22 AWG | 24 AWG | 26 AWG

## Housing Features

Housing Color Black  
Housing Material Polycarbonate

## Industry Standards

UL Flammability Rating UL 94V-0

## Mechanical Attachment

Mounting Type SL Series Faceplate

## Other

Comment With strain relief.

## Packaging Features

1375191-2

---

Packaging Method	Poly Bag
Packaging Quantity	1

## Product Availability

---

Region	Asia   Australia/New Zealand   EMEA   Latin America   North America
--------	---

## Product Type Features

---

Product Type	Modular Jack
Performance Category	Category 5e
Shielded	No
System	AMP NETCONNECT   SL 110 Series
Applies To	Panel
Cable Type	Unshielded Twisted Pair
Connector Style	Jack
Connector Type	Connector Assembly
Dust Cover	Without
Jack Type	RJ45

## Termination Features

---

Termination Method to Wire/Cable	Insulation Displacement Crimp (IDC)
Termination Style	SL Termination Tool

## Regulatory Compliance/Certifications

**Agency**  
RoHS 2011/65/EU

**Classification**  
Compliant