


DATE:	1/21/2014	3C22NS-IEWC			REVISION:	A
-------	-----------	-------------	--	--	-----------	---



DESCRIPTION: THREE CONDUCTORS 22 AWG, UNSHIELDED, PVC JACKET

CONDUCTOR: #22 7/30 TINNED COPPER (.031" OD)
INSULATION: .010" SR PVC (.051" OD)

CONSTRUCTION: TWIST THREE (3) CONDUCTORS TOGETHER
WITH A 1 1/2" LEFT HAND LAY

SHIELD: NONE

JACKET: .015" CHROME GRAY PVC
OD: .140"

JACKET PRINT
(BLACK INK): E151405 22 AWG TYPE CM 105°C (UL)...AWM 2103...C(UL)
TYPE CMG 105°C 300V FT-4...ROHS...CE

COLOR CODE: 1) BLACK 2) RED 3) GREEN

- PROPERTIES
- 1) TEMPERATURE RANGE -30 TO 105°C
 - 2) BEND RADIUS 10X CABLE DIAMETER
 - 3) PULL TENSION 16.5 LBS, MAXIMUM
 - 4) SUNLIGHT RESISTANCE YES
 - 5) VOLTAGE RATING 300 VRMS
 - 6) CAPACITANCE 23.5 PF/FT @1 KHZ, NOM COND TO COND
 - 7) INDUCTANCE 0.18 µH/FT, NOM
 - 8) CONDUCTOR DCR 16.4 Ω/1000FT @20°C, NOM



CABLE TECHNOLOGY, INC.

73 RIVER ROAD - WILLINGTON, CT 06279 - (860) 429 - 7889 FAX (860) 429 - 3615

PART NO:	TBD
REVISION:	A
ROHS	
CE	

PW: 1343