

EPIC® H-B 10 TBFH-LB

Housing design H-B. The industry standard.

The metal housing with a single lever and a direct cable entry is suitable for use in lighting and sound systems.

Info

More interior space for wiring

Single Lever version for quick locking and simple unlocking with lifting aid

Protection rating UL50E tested



Waterproof



Robust



Mechanical resistance



Industrial machinery and plant engineering



Automation & field installation

Benefits

The smallest housing with single and double lever. The right housing is available for every application

Application range

Plant engineering

Light & sound technology

Plastics industry

EPIC® H-B 10 TBFH-LB

Product features

Cable coupler hood, high version
Single lever
Straight cable entry
Versions with / without neck

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000437 ETIM 5.0 Class-Description: Housing for industrial connectors
Material:	Housing: powder-coated aluminium alloy, grey Lever: zinc-plated steel Sealing: NBR
Protection rating:	IP 65 (latched) NEMA 250, UL50E: 12 (latched)
Temperature range:	-40°C to +100°C, short-term up to +125°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.

* Prices are net prices without VAT and surcharges. Sale to business customers.



EPIC® H-B 10 TBFH-LB

Article number	Article description	PG	Neck	B	H	L	L1	L2	s
H-B housing: cable coupler hood (1 straight cable entry, single lever, high version)									
70042400	H-B 10 TBFH-LB 21	21	yes	43	74.8	73	91	88.5	50
70042600	H-B 10 TBFH-LB 29	29	yes	43	74.8	73	91	88.5	50
79042400	H-B 10 TBFH-LB M25	25	43	74.8	73	91	88.5	50	
79042600	H-B 10 TBFH-LB M32	32	43	74.8	73	91	88.5	50	

Last Update (07.01.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16