



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 16-26 3/C CU SJT 300V PAPER

STOCK NUMBER: 56-51-04-01

JACKET:

NOMINAL OUTSIDE DIAMETER: .330" in.
NOMINAL WALL THICKNESS: .030" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 3
NOMINAL OUTSIDE DIAMETER: .120" in.
NOMINAL WALL THICKNESS: .030" in.
INSULATION COMPOUND: Polyvinyl Chloride
COPPER: 16 AWG 26X.010" SBC

TEMPERATURE:

105°C - MAX
-20°C - MIN

FILLERS:

Reinforced paperfiller

COMPLIANCE:

RoHs

PRINT:

INDENT

PRINT DESCRIPTION:

(UL) VW-1 E46194 (M) SJT 3/C 16 AWG (1.31mm²) 105°C 300V (CSA) FT1,FT2 LL90458 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013