



# Coast™ Custom Cable

(310) 639-9473 Phone (310) 763-2225 Fax

Part Number: **09-1079RA WH199**

Revision: **A**

End Use Customer: **N/A**

Customer P/N: **N/A**

IP Owner: **IEWC**

Customer Revision: **None**

## Lead Wire Specification

### 16 AWG Lead Wire - White

#### CONDUCTOR

**Wire Size & Type:** 16 (7x95/44) AWG Tinned Copper

**Nom. Wire Diameter:** 0.066

#### INSULATION

**Insulation Type:** FEP - White

**Nom. Ins Thickness:** 0.006

**Lead Wire Diameter:** **0.078**

**Tolerance (+/-):** 0.003

#### TESTS

**Test 1:** Physical/Dimensional

**Test 2:** Spark - 3000VAC

#### MISCELLANEOUS

**Voltage:** 300Vrms

**Temperature:** -40°C to 150°C

**Put Ups:** Bulk, May Contain Multiple Lengths Per Reel

**Reel:** Plastic

**Print:** None

**Colors:** Munsell® Component Limits of Deviation

#### ENVIROMENTAL

**RoHS Directive:** European Directive 2011/65/EU

#### APPROVALS

**Final Product:** None



**Rev. A**

Added optional FEP 60-1000-07 (60-1000-01), Removed wood reel

Jose Q. 10/25/2011

**UNCONTROLLED COPY**

**Dimensions in inches unless otherwise specified**

**UNCONTROLLED COPY**

**.XXX = +/- .005 .XX = +/- .02 .X = +/- .1**

**Prepared By:** Eli Siliga

**Customer Approval:**

**Date:** 6/1/2017

**Title:**

**Date:**

#### PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.