

157-00232

HellermannTyton

Article Number: 157-00232

Description: 1-Piece Cable Tie w/Oval Fir Tree, Mounting Hole Dia. 6.2–13.0mm, PA66HIRHS, Black, 500/bag



Base Data	
Local Order Number	157-00232
Type	T50ROSFTOVALR
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> • The fir tree branch design on all four sides makes a 360-degree interface with the panel, creating a more secure fit into the hole. • The disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt. • The oval hole fir tree fits 4 common automotive oval hole sizes. • The specific connector slot on this part reduces rattle and movement of clip to the wire harness connector.
Quantity Per	bag
Product Description	The one-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables. The innovative design of the fir tree creates an interface with four different size holes that are common in the automotive industry. The fir tree branch design on all four sides makes a 360-degree interface with the panel, creating a more secure fit into the hole. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.
GLOBAL PART NAME	T50ROSFTOVALR-PA66HIRHS-BK
Short Description	1-Piece Cable Tie w/Oval Fir Tree, Mounting Hole Dia. 6.2–13.0mm, PA66HIRHS, Black, 500/bag
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	225N
Length L (Imperial)	8.6"
Length L (Metric)	219.3mm
Fixation Method	Fir Tree for oval holes
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.20"
Width W (Metric)	5.1mm

157-00232



Product Dimensions	Bundle Diameter Min. (Imperial)	0.08"
	Bundle Diameter Min. (Metric)	2.0mm
	Bundle Diameter Max. (Imperial)	1.97"
	Bundle Diameter Max. (Metric)	50.0mm
	Panel Thickness Max. (Imperial)	0.24"
	Panel Thickness Max. (Metric)	6.0mm
	Panel Thickness Min. (Imperial)	0.02"
	Panel Thickness Min. (Metric)	0.6mm
	Mounting Hole Diameter D (Imperial)	0.24 x 0.48 " 0.25 x 0.50 " 0.25 x 0.50 " 0.27 x 0.47 "
	Mounting Hole Diameter D (Metric)	6.2 x 12.2 mm 6.5 x 12.5 mm 6.5 x 13.0 mm 7.0 x 12.0 mm
	Mounting Hole Diameter D Min. (Imperial)	0.24"
	Mounting Hole Diameter D Max. (Imperial)	0.51"
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces