



**Description:** Six 14 AWG Conductors  
Overall Foil Shield and PVC Jacket

**Date:** 7/26/2017

**JM Part Number:** JM57886  
**Reference:** 32043552

---

**Components** Six 14 AWG Insulated Conductors

Conductor: 14 AWG, 41/30 bare copper

Insulation: .022" nominal wall of PVC (see color code below) .122"

---

**Cable Construction**

Cabling: Six conductors cabled together with fillers as needed

Drain Wire: 16 AWG, 26/30 tinned copper

Foil Shield: Aluminum-Mylar tape, Aluminum side In

Jacket: .063" nominal wall of Gray PVC .496"

---

**Print (Black Inkjet)**

E66440 6/C 14 AWG SHIELDED  $\Omega$  AWM 2501 105C 600V VW-1  
--- LL41103 CSA AWM I/II A/B 105C 600V FT1 --- CE ROHS

---

**Color Code**

- |          |          |
|----------|----------|
| 1. Black | 4. Green |
| 2. White | 5. Brown |
| 3. Red   | 6. Blue  |

---

**Requirements**

Temperature: 105C  
Voltage: 600V

Approvals: UL AWM Style 2501, VW-1  
CSA AWM, FT1  
CE - LVD RoHS Compliant  
(2011/65/EU & EU 2015/863)

Written By:	rac	7/26/2017	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				